





Rotating cleaning nozzle "Whirly" Series 569

Series 569

The design of the stainless steel Whirly has been proven over time. The flat jet nozzles provide effective cleaning. Available in a wide range of connection sizes and flow rates. Also available in ATEX approved version.



To see video

Scan the QR-code
or go to:
www.lechlerusa.com

	Max. tank diameter [ft]	0	5	10	15	20	25
--	--------------------------------	---	---	----	----	----	----



Materials
Stainless steel
AISI 316L, PEEK, Rulon
641



Max. temperature
284°F/ 140°C
194°F/ 90°C ATEX version



Recommended operating pressure
30 psi




Installation
Operates in every direction. Requires at least 30 psi or more for operation with horizontal installation. ATEX version operates in vertical position only.




Filtration
Line strainer with a mesh size of 0.1 mm/ 170 Mesh



Bearing
Double ball bearing made of stainless steel







Overview of the tank diameter, depending upon the pressure of series 569



3/4" NPT female thread

Slip-on connection
ASME - BPE 1997 (OD-Tube)

1" Tri-Clamp

Spray angle 	Ordering no.						Free Passage (in.)	Flow Rate (Gallons Per Minute)					Max. tank diameter [ft]
	Type	Connection						20 psi	30 psi	liters per minute 2 bar	40 psi	60 psi	
		3/4" Female NPT	3/4" OD Slip-on	1" OD Slip-on	1 1/2" OD Slip-on	Tri-Clamp							
270° 	569.055.1Y	BL	TF07	TF10	TF15	10	.141	11	13	48	15	18	6
	569.135.1Y	BL	TF07	TF10	TF15	10	.189	16	19	71	22	27	7
	569.195.1Y	BL	TF07	TF10	TF15	10	.220	21	26	97	30	37	9
270° 	569.056.1Y	BL	TF07	TF10	TF15	10	.141	11	13	48	15	18	6
	569.106.1Y	BL	TF07	TF10	TF15	10	.189	13	16	58	18	22	7
	569.196.1Y	BL	TF07	TF10	TF15	10	.220	21	26	97	30	37	9
360° 	569.059.1Y	BL	TF07	TF10	TF15	10	.126	11	13	48	15	18	6
	569.139.1Y	BL	TF07	TF10	TF15	10	.141	16	19	71	22	27	7
	569.199.1Y	BL	TF07	TF10	TF15	10	.189	21	26	97	30	37	9
	569.279.1Y	BL	TF07	TF10	TF15	10	.280	32	39	145	45	55	10

The maximum tank diameter shown above applies for the recommended operating pressure and is indicative only. The cleaning result is also affected by the type of soiling.


Information on operation



- Operation with compressed air purge only for short-term usage. Operation above the recommended operating pressure means higher wear and smaller droplets. This might have adverse effects on the cleaning result.


Slip-on information

- R-clip made of stainless steel AISI 316L is included (Ordering no.: 095.022.1Y.50.60.E).
- Depending on diameter of the adapter the flow rate can increase due to leakage between the connection and rotating cleaning nozzle.

Example of ordering with ATEX approval. FDA and (EG) 1935/2004 conform.


 **FDA compliant**

Unit group / category / zones:
 II 1G Ex h LLB T6... T3 Ga
 II 1D Ex h IIIC T85 °C...T150 °C Da


 **ATEX**

Example of ordering: Type + Connection = Ordering no.
of Ordering: 569.055.1Y.XX.EX + BL = 569.055.1Y.BL.EX

Example of ordering with FDA and (EG) 1935/2004 conform.

 **FDA compliant**

All Materials are suitable for contact with food.



Example of ordering: Type + Connection = Ordering no.
of ordering: 569.103.1Y.XX + BL = 569.103.1Y.BL